ADAPTER BSPP THREAD FEMALE TO CLAMP

TC imperial - BSPP Thread Female

Adapters are available as either male or female and are supplied with a BSPP thread. All threaded adapters are manufactured from solid 316L bar stock. This offers both excellent material properties and guarantees good controllable surface finishes. The flanged clamping side of the BSPP adapters is dimensioned and manufactured to mate up' directly with corresponding ferrules.

Male adapters are manufactured with a tapered thread or parallel threads. Female adapters are manufactured with a parallel thread. All adapters are supplied with machined flats for wrench applications and to aid ease of assembly.



Sizes	see table	
Connections	Tri-clamp	
Material	1.4404 (316L)	
Finishes	Interior surfaces SF1	
Certificates (st.)	3.1 material	
Certificates (opt.)	2.2 surface finish	

B ØD ØC

Clamp	Thread	Flange	Mating	L
Size	В	С	D	
1/2"	1/8"	25	10.0	25
	1/4"	25	10.0	25
	3/8"	25	10.0	25
	1/2"	25	10.0	30
	3/4"	25	10.0	30
3/4"	1/8"	25	16.0	25
	1/4"	25	16.0	25
	3/8"	25	16.0	25
	1/2"	25	16.0	30
	3/4"	25	16.0	30
1"	1/8"	50.5	22.0	25
	1/4"	50.5	22.0	25
	3/8"	50.5	22.0	25
	1/2"	50.5	22.0	25
	3/4"	50.5	22.0	25
	1"	50.5	22.0	25
1½"	1/8"	50.5	35.0	25
	1/4"	50.5	35.0	25
	3/8"	50.5	35.0	25
	1/2"	50.5	35.0	25
	3/4"	50.5	35.0	25
	1"	50.5	35.0	35
2"	1/2"	64	47.6	25
	3/4"	64	47.6	25
	1"	64	47.6	25
	1½"	64	47.6	25
	2"	64	47.6	25





RX: F-D

These are standard items. We also deliver other sizes, according to ISO, DIN and SMS. For more and the latest information use the QR-code to go to the website.